




| Position | Qty. | Description |
|----------|------|--|
| | 1 | <p>UPS 25-55 N 180</p>  <p style="text-align: center;">Note! Product picture may differ from actual product</p> <p>Product No.: 95906772</p> <p>The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump has 3-step speed selector. The pump is characterized by:</p> <ul style="list-style-type: none"> * Ceramic shaft and radial bearings. * Carbon axial bearing. * Stainless steel rotor can and bearing plate. * Corrosion-resistant impeller, Composite, PES/PP. * Stainless steel pump housing. <p>The motor is a 1-phase motor. No additional motor protection is required.</p> <p>Liquid: Pumped liquid: Water Liquid temperature range: -25 .. 110 °C</p> <p>Technical: TF class: 110</p> <p>Materials: Pump housing: Stainless steel Pump housing: DIN W.-Nr. 1.4301 Impeller: Composite, PES/PP</p> <p>Installation: Amb. max at 80 dgr C liquid: 40 °C Maximum operating pressure: 10 bar Pipe connection: G 1 1/2 Pressure stage: PN 10 Port-to-port length: 180 mm</p> <p>Electrical data: Power input in speed 1: 65 W Power input in speed 2: 80 W Max. power input: 85 W Mains frequency: 50 Hz Rated voltage: 1 x 230 V</p> |



Company name: -
Created by: -
Phone: -
Fax: -
Date: -

| Position | Qty. | Description |
|----------|------|--|
| | | Current in speed 1: 0.3 A Current in speed 2: 0.36 A Current in speed 3: 0.38 A Capacitor size - run: 2.5 μ F Enclosure class (IEC 34-5): 44 Insulation class (IEC 85): F |
| | | Others: Net weight: 4.6 kg Gross weight: 4.7 kg Shipping volume: 0.008 m3 Energy label: C |



95906772 UPS 25-55 N 180 50 Hz

