



# SUNVIC

## comfort in control

### VKL 2000 Rod Thermostat



- 16 amp rating
- Simple 2 wire connection
- Manual reset model
- Available in three standard lengths

### Selection Guide

Model	Stem Length	Range (°C)	Differential (°C)	Voltage	Current Rating (amps)
VKL 2201	7" / 178mm	40-80	10	230V AC	16A
VKL 2251	7" / 178mm	45-85	Manual Reset	230V AC	16A
VKL 2301	11" / 280mm	50-80	6	230V AC	16A
VKL 2303	11" / 280mm	25-65	6	230V AC	16A
VKL 2351	11" / 280mm	35-85	Manual Reset	230V AC	16A
VKL 2401	18" / 457mm	50-80	5	230V AC	16A

### VKL 2000 Series Technical Specification

Contacts:	Single pole
Function:	Break on temperature rise
Voltage:	230V AC
Load Current:	16A

## Rod Thermostats

SUNVIC CONTROLS LIMITED  
Units 1 & 2, Block 1, 251 Low Waters Road, Cadzow Industrial Estate,  
Hamilton, ML3 7QU, Scotland, UK  
Tel: +44 (0)1698 308302 Fax: +44 (0)1698 813583  
Helpline: +44 (0)1698 810945 Email: sales@sunvic.co.uk



# SUNVIC

## comfort in control

### VK 4000 Rod Thermostat



- 20 amp rating
- Simple 2 wire connection
- Available in three standard lengths

#### Selection Guide

Model	Stem Length	Range (°C)	Differential (°C)	Voltage	Current Rating (amps)	Features
VK 4251	7" / 178mm	10-88	10	230V AC	20A	
VK 4252	7" / 178mm	10-88	10	230V AC	20A	Pocket Clip
VK 4253	7" / 178mm	40-110	10	230V AC	20A	
VK 4254	7" / 178mm	40-110	10	230V AC	20A	Pocket Clip
VK 4351	11" / 280mm	40-88	6	230V AC	20A	
VK 4352	11" / 280mm	40-88	6	230V AC	20A	Pocket Clip
VK 4353	11" / 280mm	70-120	6	230V AC	20A	
VK 4354	11" / 280mm	70-120	6	230V AC	20A	Pocket Clip
VK 4451	18" / 457mm	55-85	5	230V AC	20A	

#### VK 4000 Series Technical Specification

Contacts:	Single pole
Function:	Break on temperature rise
Voltage:	230V AC
Load Current:	20A – not recommended for currents below 0.5A AC

SUNVIC CONTROLS LIMITED  
Units 1 & 2, Block 1, 251 Low Waters Road, Cadzow Industrial Estate,  
Hamilton, ML3 7QU, Scotland, UK  
Tel: +44 (0)1698 308302 Fax: +44 (0)1698 813583  
Helpline: +44 (0)1698 810945 Email: sales@sunvic.co.uk